

NAME

wcrtsrc

PURPOSE

Creates a source on the event server.

SYNOPSIS

Wcrtsrc [-S *server*] [-b *bitmap*] [-l *label*] *source*

DESCRIPTION

The **wcrtsrc** command appends a source to the current source list on the event server. The *source* name is checked to be sure it is not a duplicate before it is added to the list. Sources send event information to the Enterprise Console via event adapters. The event adapter defines the name for a source.

Authorization

senior

Arguments

- | | |
|------------------|---|
| -S <i>server</i> | Specifies the name of the event server in name registry format. The default is the local event server. To specify a remote server, enter @EventServer#<i>tmr</i> , where <i>tmr</i> is the name of a xxxxxx xxxxx xxxxx (TMR). |
| -b <i>bitmap</i> | Displays the specified bitmap on the event console. The bitmap must be the name of a bitmap stored at the server. |
| -l <i>label</i> | Uses the specified label as the name of the source on event consoles. If this argument is not specified, the value specified in the <i>source</i> argument is used as a label. |
| <i>source</i> | Specifies the name of the source to create. The name must correspond to the name specified by the event adapter. |

EXAMPLES

The following example adds the **LOGFILE** source to the local TMR and labels the source **Logfile**:

```
Wcrtsrc -l "Logfile" LOGFILE
```

SEE ALSO

wdelsrc, wlssrc, wsetsrc